

Mr. Cody Walker Associate Engineering Geologist North Coast Regional Water Quality Control Board 5550 Skylane Boulevard, Suite A Santa Rosa, California 95403 September 20, 2006

Re: Third Quarter 2006 Groundwater Monitoring Report

Cedar Stock Resort 45810 State Highway 3 Trinity Center, California RWQCB case # 1TTR033 Blue Rock Project No. NC-017

Dear Mr. Walker,

This report presents the results of the Third Quarter 2006 groundwater monitoring activities at Cedar Stock Resort located at 45810 State Highway 3, Trinity Center, California. (site) (Figure 1), and was prepared for Mr. Cliff Johanssen of Boots and Boats Inc. by Blue Rock Environmental Inc. (Blue Rock).

## Background

Site Description

Cedar Stock Resort is located adjacent to Trinity Lake in Trinity County California (Figure 1). The site is bounded by open forest land with some residential development. Cedar Stock Resort consists of a developed dock and additional parking areas around the former UST locations and a Lodge/Restaurant above the site. There are also various buildings near the site used for rental cabins, boat storage and residences. The resort uses a septic system located approximately 500 feet north of the former UST locations for sewage disposal. Drinking water is supplied by a well located about 1/4 mile north of the former USTs. The two gasoline USTs were previously located on the eastern side of the marina parking area (Figure 2).

The site slopes moderately to steeply toward the east. The Trinity Lake shoreline (high water line at 2,370 feet elevation above mean sea level (msl)) comprises the eastern boundary of the property. To the west, the property rises to 2,600 feet in elevation.

## Site History

Cedar Stock Resort was developed in 1962 as a boat launching and storage facility and resort destination. The site was leased from the U.S. Department of Agriculture (USDA) by Boots and Boats Inc. in the early 1970s. In 1980 or 1981, two 5,000-gallon underground gasoline storage tanks (UST) were installed to supply fuel to boat traffic on Trinity Lake. Fuel was delivered via above ground piping to dispensers located on the dock.

## Site Investigation and Corrective Action History

In September 1994, the two 5,000 gallon USTs were removed by Evans Construction (Evans). As evidenced by analysis of soil removed from the excavation, concentrations of total petroleum hydrocarbons as gasoline (TPHg) ranged to 2,000 parts per million (ppm). The tank cavity was overexcavated to a depth of approximately 40 feet below ground surface (bgs) to remove hydrocarbons acting as a source of groundwater contamination. Due to adverse site conditions no further overexcavation was performed. The excavation was subsequently backfilled with clean fill.

In an effort to evaluate the lateral extent of petroleum hydrocarbon impact to site soil and groundwater, Clearwater Group (Clearwater) supervised the installation of five soil borings (B-1 to B-5) and four monitoring wells (MW-1 to MW-4) in 1996 and 1997. Gasoline constituent contamination in soil and groundwater were detected in boring B-1 approximately 25 feet downgradient of the former excavation. Analysis of groundwater samples indicated concentrations of TPHg at 2,400 micrograms per liter (μg/L), MTBE at 2,000 μg/L, and benzene at 940 μg/L. A grab groundwater sample collected from boring B-5 (40 feet northeast of the UST excavation) indicated concentrations of TPHg at 1,900 μg/L, MTBE at 41 μg/L, and benzene at 160 μg/L. Quarterly groundwater monitoring and sampling of the monitoring wells was performed through the remainder of 1997 and continued through 1998. As the site was considered a low priority by the North Coast Regional Water Quality Control Board (NCRWQCB), no direction for additional quarterly monitoring was provided. Subsequently, no quarterly monitoring was performed in 1999. At the direction of Dean Prat of the NCRWQCB quarterly groundwater monitoring was resumed in January 2000.

On May 4, 2000, in an effort to better evaluate groundwater flow characteristics at the site, Clearwater supervised Diamond Core Drilling of Redding, California in the installation of two additional monitoring wells (MW-5 and MW-6) to the north and east of the former excavation. Well installation activities were approved verbally by Mr. Dean Pratt of the NCRWQCB. Results of this investigation are presented in Clearwater's *Monitoring Well Installation and Groundwater Monitoring Report Second Quarter 2000* dated July 18, 2000. Well construction data are presented in Table 1.

On March 4 and 5, 2002, Clearwater supervised, Mitchell Drilling Environmental of Rancho Cordova, California in the drilling four soil borings to a depth of approximately 60 feet bgs (Figure 2). The purpose of the proposed additional investigation was to provide the data needed for the preparation of the required Corrective Action Plan (CAP). Results of this investigation are presented in Clearwater's Corrective Action Plan (CAP) / Sensitive Receptor Survey / Additional Investigation Report dated April 26, 2002. In a letter dated June 4, 2002, the NCRWQCB approved the CAP which outlined soil vapor extraction (SVE) as the preferred remedial alternative to treat sorbed-phase contamination and monitored natural attenuation for treating dissolved-phase contamination and requested the submittal of a workplan to perform an SVE pilot study.

Clearwater subsequently prepared and submitted a Workplan for Vapor Extraction Pilot Study dated August 10, 2002. The workplan was approved in a NCRWQCB letter dated September 9, 2002. The pilot study was performed in October 2002. The results of the monitored natural attenuation study

were favorable; however, the results of the SVE test were not favorable. Therefore, low vacuum SVE was not considered to be a technically viable remedial alternative. Results of the pilot study and natural attenuation feasibility study were submitted in Clearwater's Second Quarter 2003 and Remedial Action Plan dated July 21, 2003.

In a letter dated September 25, 2003, the NCRWQCB concurred with Clearwater's evaluation of the monitoring data and recommendation to continue natural attenuation monitoring for a one year period. In the letter, the NCRWQCB requested a summary report be submitted following a one year period and should include an estimate of time for natural attenuation to restore beneficial uses of groundwater at the site and the evaluation of at least one additional remedial alternative and a cost comparison of the remedial alternatives.

In May 2004, Blue Rock was retained to continue site activities. Blue Rock performed the Second Quarter 2004 groundwater monitoring event and subsequently submitted the *Remedial Action Plan Addendum / Summary Report / Second Quarter 2004 Groundwater Monitoring Report* dated July 20, 2004 which conveyed the data requested in the September 25, 2003, NCRWQCB letter and requested the site be evaluated for closure. The NCRWQCB denied the closure request in a letter dated September 8, 2004 and requested groundwater monitoring be performed on a semi annual basis.

From October 31, to November 4, 2005 Blue Rock performed a 5 day dual-phase extraction (DPE) event per the *Workplan for Mobile High-Vacuum Dual-Phase Extraction Treatment* dated August 18, 2005 which was approved in the NCRWQCB letter dated September 15, 2005. The DPE event was successful in demonstrating that TPHg, BTEX, and MTBE can be removed from the subsurface using this technology. Influent concentrations of TPHg averaged approximately 350 mg/m³. In the vapor-phase, TPHg removal rates ranged from 0.7 to 4.2 lbs/day and MTBE removal rates ranged from 0.01 to 0.03 lbs/day. DPE appeared to be successful at lowering concentrations of target analytes at the extraction point based on the results of the pre-test and post-test samples collected from MW-1. Specifically, TPHg was reduced from 730 μg/L (pre-test 10/31/05) to 260 μg/L (post-test 11/4/05), benzene was reduced from 5.8 μg/L (pre-test 10/31/05) to 1.6 μg/L (post-test 11/4/05). Data collected during this event were reported in the *Dual-Phase Extraction Treatment Report* dated November 28, 2005.

## Field and Laboratory Activities - Third Quarter 2006

## Groundwater Monitoring Activities

On September 6, 2006 six wells (MW-1 through MW-6) were monitored and sampled. Prior to sampling, an electronic water level indicator was used to gauge depth to water in each well, accurate to within ±0.01-foot. A downhole dissolved oxygen (DO) meter was used to measure concentrations of DO. Due to the depth to water in MW-2, 3, 5 and 6 being lower than the depth the DO meter will reach, no DO readings could be collected from these wells. All wells were checked for the presence of light non-aqueous phase liquid (LNAPL) petroleum prior to purging. No measurable thicknesses of LNAPL were observed on groundwater in any of the wells.

In preparation for sampling, the wells were purged of groundwater until sampling parameters (temperature, pH, and conductivity) stabilized. Following recovery of water levels to approximately 80% of their static levels, groundwater samples were collected from the wells using disposable polyethylene bailers and transferred to laboratory supplied containers. Sample containers were labeled, documented on a chain-of-custody form, and placed on ice in a cooler for transport to the project laboratory.

Purging instruments were cleaned between use by an Alconox® wash followed by double rinse in clean tap water to prevent cross-contamination. Purge and rinseate water was stored on-site in labeled 55-gallon drums pending future removal and disposal.

Groundwater monitoring and well purging information is presented on Gauge Data/Purge Calculations and Purge Data sheets (Appendix A).

## Groundwater Sample Analyses

Groundwater samples were analyzed by Kiff Analytical (Kiff), a DHS-certified laboratory, located in Davis, California, for the following analytes:

TPHg, BTEX, MTBE by EPA Method 8260B

## Groundwater Monitoring Results - Second Quarter 2006

## Groundwater Flow Direction and Gradient

Static groundwater in the wells was present beneath the site at depths ranging from approximately 20.02 (MW-5) to 28.02 (MW-2) feet bgs. Gauging data, combined with well elevation data, were used to calculate groundwater elevations, and to generate a groundwater elevation and gradient map. The groundwater flow direction was calculated to be toward the northeast at a gradient of 0.25 ft/ft in the area of the former USTs and becoming more northerly downgradient (Figure 3). The groundwater gradient and flow direction is consistent with previous measurements.

## Groundwater Contaminant Analytical Results

LNAPL: None

TPHg concentration: <50 μg/L (MW-2 to MW-6) to 680 μg/L (MW-1) MTBE concentration: <0.5 μg/L (MW-4 & MW-5) to 340 μg/L (MW-1)

Benzene concentration: <0.5μg/L (MW-3 to MW-6) to 38 μg/L (MW-1)

Groundwater sample analytical results are shown graphically on Figures 4 and 5. Cumulative groundwater sample analytical results are summarized in Table 2. Copies of the field notes, laboratory report and chain-of-custody form are presented in Appendix A and B.

## Remarks

Groundwater sample analytical results are consistent with previous groundwater data. The plume of dissolved-phase hydrocarbons appears to be stable with decreasing and/or stable concentrations of target analytes.

## Natural Attenuation Monitoring Program

## First Order Decay Rates

Trends in dissolved-phase concentrations were evaluated for MW-1 and MW-2, the only historically impacted wells. TPHg, benzene, and MTBE for those wells were plotted against time since January 2000 (the highest concentration of TPHg recorded). An exponential equation was fitted to each data set to calculate first-order decay rates (Appendix C). The method presented by Buscheck, O'Reilly, and Nelson (1993) was used to calculate first-order decay rates by the following equation:

$$C(t) = C_0 e^{-(kt)}$$

Where,

C(t) is concentration as a function of time (t)

 $C_0$  = is concentration as t = 0

 $k = is the decay rate (t^{-1})$ 

Trend lines fit to these data sets indicate the following contaminant decay rates. The R<sup>2</sup> values indicate the "goodness of fit" of the trend line/equation to the data (R<sup>2</sup> values greater than 0.75 are generally considered a good fit):

Cumulative Analytical Data

Well	TPHg Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	Benzene Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	MTBE Decay Rate (day-1)	R² Value
MW-1	0.001	0.471	0.0024	0.617	0.0008	0.608
MW-2	0.012	0.544	0.0015	0.420	0.0016	0.313

As shown in the attached charts (1a/b/c and 2a/b/c), the estimated time to reach water quality goals based on the above decay rates for TPHg, benzene and MTBE in MW-1 are approximately 7 years, 3

years and 13 years respectively. It should be noted that concentrations of target analytes in MW-2 have reached water quality goals with the exception of low residual MTBE concentrations.

As part of the evaluation of decay rates of dissolved phase contaminants, Blue Rock divided the above data set into two categories based on depth to water. Variations in target analyte concentrations have been observed relative to the depth groundwater is present with generally higher concentrations of target analytes when depth to groundwater in MW-1 falls below 25 feet bgs (Charts 3a and 3b).

Low Groundwater (Depth to Water Greater Than 25 feet bgs) Analytical Data

Well	TPHg Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	Benzene Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	MTBE Decay Rate (day-1)	R <sup>2</sup> Value
MW-1	0.009	0.345	0.0027	0.627	0.0006	0.436

High Groundwater (Depth to Water Less Than 25 feet bgs) Analytical Data

Well	TPHg Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	Benzene Decay Rate (day <sup>-1</sup> )	R <sup>2</sup> Value	MTBE Decay Rate (day-1)	R <sup>2</sup> Value
MW-1	0.0012	0.653	0.0022	0.821	0.0009	0.769

As indicated in the above tables, the first order decay rates for low groundwater events are similar to those for the entire data set. Additionally, R<sup>2</sup> values are similar indicating a poorer fit and a less reliable extrapolation. Alternatively, when only high groundwater analytical data are used in the extrapolation, decay rates are similar. Additionally, the high groundwater sets produce significantly higher R<sup>2</sup> values than those for low groundwater data sets. As shown in the attached chart (3b), the estimated time to reach water quality goals based on the high groundwater decay rates for TPHg, benzene and MTBE in MW-1 are approximately 6 years, 3 years and 10 years respectively.

Although first order decay rates indicate that the dissolved-phase concentrations continue to decline, they may not reach Clean-up Goals in a reasonable timeframe when extrapolated from current concentrations. As stated in the previous quarterly report, further reduction in existing concentrations would result in a shorter estimated timeframe to meet Clean-up Goals.

It should be noted that the plume of residual dissolved-phase gasoline range hydrocarbons remains stable with no significant migration. This has been evidenced by concentrations of target analytes below or slightly above laboratory detection limits in downgradient and cross gradient monitoring points for the duration of the quarterly groundwater monitoring program.

## Conclusions and Recommendations

- The dissolved-phase plume continues to remain stable with an observed increase in concentrations of target analytes in MW-1 and MW-2 this quarter.
- In the Second Quarter 2006 groundwater monitoring report, Blue Rock recommended performing
  one additional Mobile HDPE remedial event during low groundwater conditions in October 2006
  (when site operations allow use of the mobile unit) as a remedial polisher for a two week duration
  to bring dissolved-phase concentrations nearer to groundwater quality goals for future site
  closure. The performance of this event was approved verbally by the NCRWQCB in a September
  15, 2006 telephone conversation, pending written approval. This event is scheduled to occur in
  late October or early November 2006.
- The site is currently being monitored on a quarterly basis per the NCRWQCB directives. The
  next quarterly sampling event is scheduled for December 2006. Groundwater samples will be
  analyzed for TPHg, BTEX and MTBE by EPA Method 8260B.

## References

Buscheck, T.E., O'Reilly, K.T., and Nelson, S.N. 1993. Evaluation of Intrinsic Bioremediation at Field Sites. Proceedings of the Conference of Petroleum Hydrocarbons and Organic Chemicals in Ground Water, National Groundwater Association/API, Houston, TX. November 10-12.

## Certification

This report was prepared under the supervision of a California Professional Geologist at Blue Rock. All statements, conclusions, and recommendations are based upon published results from past consultants, field observations by Blue Rock, and analyses performed by a state-certified laboratory as they relate to the time, location, and depth of points sampled by Blue Rock. Interpretation of data, including spatial distribution and temporal trends, are based on commonly used geologic and scientific principles. It is possible that interpretations, conclusions, and recommendations presented in this report may change, as additional data become available and/or regulations change.

Information and interpretation presented herein are for the sole use of the client and regulating agency. The information and interpretation contained in this document should not be relied upon by a third party.

The service performed by Blue Rock has been conducted in a manner consistent with the level of care and skill ordinarily exercised by members of our profession currently practicing under similar conditions in the area of the site. No other warranty, expressed or implied, is made.

If you have any questions regarding this project, please contact us at (707) 441-1934.

Sincerely,

Blue Rock Environmental, Inc.

Prepared by:

Andrew LoCicero Project Scientist Reviewed by:

Brian Gwinn, PG Principal Geologist

## Attachments:

Table 1: Well Construction Data

Table 2: Groundwater Elevation and Analytical Data

Table 3: Intrinsic Bioremediation Data

Figure 1: Site Location Map

Figure 2: Site Plan

Figure 3: Groundwater Elevations and Gradient – September 6, 2006 Figure 4: Dissolved-Phase TPHg Distribution - September 6, 2006 Figure 5: Dissolved-Phase MTBE Distribution - September 6, 2006

Figure 6: Intrinsic Bioremediation Data - September 6, 2006

Appendix A: Blue Rock Gauge/Purge Calculations and Well Purging Data field sheets

Appendix B: Laboratory Analytical Report and Chain-of-Custody Form

Appendix C: First Order Decay Rate Graphs

### cc:

Cliff Johanssen HCR Box 519 Trinity Center, CA 96091

Leslie Ross Environmental Engineer USDA United States Forest Service 3644 Avetech Parkway Redding, CA 96002

Mr. Peter Hedtke Trinity County Environmental Health Department PO Box 476 Weaverville, CA 96093

Mr. Howard C. Rice 359 Spring Beauty Ct. Windsor, CA 95492 J. Sharon Heywood Forest Supervisor C/O USDA, Forest Service Shasta-Trinity National Forest 3644 Avetech Parkway. Redding, CA 96002



## Table 1 WELL CONSTRUCTION DATA

Cedar Stock Resort 45180 State Highway 3 Trinity Center, California Project No. NC-017

Well Identification	Date Intstalled	Intstalled by	Casing Diameter (inches)	Total Depth (feet)	Blank Interval (feet)	Screened Interval (feet)	Slot Size (inches)	Filter Pack (feet)	Bentonite Seal (feet)	Cement (feet)
			(anemes)	(2001)	(1001)	(1000)	(inches)	(1000)	(1001)	(icct)
MW-1	11/18/97	Clearwater	2	40	0-20	20-40	0.02	18-40	16-18	0-16
MW-2	11/18/97	Clearwater	2	40	0-20	20-40	0.02	18-40	16-18	0-16
MW-3	11/18/97	Clearwater	2	40	0-20	20-40	0.02	18-40	16-18	0-16
MW-4	11/18/97	Clearwater	2	40	0-20	20-40	0.02	18-40	16-18	0-16
MW-5	8/30/00	Clearwater	2	35	0-15	15-35	0.02	14-35	12-14	0-12
MW-6	8/30/00	Clearwater	2	35	0-15	15-35	0.02	14-35	12-14	0-12

Well No.	Sampling Date	TOC (feet)	DTW (feet)	GWE (feet)	TPHg (μg/L)	B (μg/L)	T (μg/L)	E (µg/L)	X (µg/L)	MTBE (μg/L)			ETBE (µg/L)			Eth. (µg/L)
MW-1	11/23/97	2383.6	28.41	2355.14	4,500	3,100	11	13	36	2,200						
141 11 -1	12/22/97	2383.6	29.06	2354.49	4,500	3,100		15	50	2,200	-					
Screen	2/1/98	2383.6	31.46	2352.09	-			-		_	-		-	-		
20'-40'	2/26/98	2383.6	34.36	2349.19	2,300	65	< 0.5	0.6	< 0.5	390	-			_	-	
10	3/14/98	2383.6	32.68	2350.87	2,500		-0.0	0.0	-0.5	330	_					
	4/25/98	2383.6	26.59	2356.96		-			_		-					
	5/16/98	2383.6	24.12	2359.43	910	180	7.2	1.3	6.7	110			-	_		-
	6/6/98	2383.6	24.79	2358.76	710	100					-					
	7/18/98	2383.6	22.23	2361.32			-									
	9/3/98	2383.6	15.81	2367.74	95	25	< 0.5	< 0.5	0.65	26						
	10/2/98	2383.6	16.44	2367.11			-0.2	-0-2	0.05	20	-			_		
	11/27/98	2383.6	23.77	2359.78										_		
	12/15/98	2383.6	21.18	2362.37	1,100	260	4.4	5.6	7.3	95	_	-	-	_		
	1/11/00	2383.6	23.25	2360.30	17,000	4,600	27	320	254	1,700	-		-			
	5/4/00	2383.6	18.29	2365.26	17,000			520	254	1,700	-	-	_	_		
	6/1/00	2383.6	15.97	2367.58	3,140	2,250	6.9	62	68	861	-				-	**
	9/26/00	2383.6	21.75	2361.80	11,900	4,750	17	174	127	2,930	_	-				
	12/22/00	2383.6	25.49	2358.06	4,890	1,620	7.6	28.2	36.5	1,860	-	-		-		
	3/30/01	2383.6	27.05	2356.50	1,900	1,130	2.5	1.6	3.1	939	-	-	_	_	_	-
	6/13/01	2383.6	26.04	2357.51	4,700	1,400	3.0	2.1	3.7	1,100		-		-	_	-
	9/21/01	2383.6	28.73	2354.82	4,300	1,400	<5	<5	<5	1,200	84	<5	<5	<5	<2,000	<50
	12/15/01	2383.6	36.39	2347.16	410	15	<1	<1	<1	360	370	<1	<1	<1	<1,700	<10
	3/15/02	2383.6	29.76	2353.79	2,400	440	<5	<5	<5	1,400	370	-			-1,700	
	6/26/02	2383.6	26.78	2356.77	5,600	1,600	<10	<10	<10	1,700		-	-		-	
	9/25/02	2383.6	29.38	2354.17	6,400	1,300	<10	<10	<10	1,800			_		_	-
	12/12/02	2383.6	Dry					-10		1,000		-	-		-	-
	(3/20/03)	2421.70	32.42	2389.28	<500	<5	<5	<5	<5	1,400				-	_	-
	6/11/03	2421.70	23.62	2398.08	420	23	<1	<1	<1	550						-
	9/24/03	2421.70	23,47	2398.23	2,300	220	<1.5	<1.5	<1.5	710						
	12/15/03	2421.70	27.95	2393.75	2,600	120	<2	<2	<2	940		-				
	3/4/04	2421.70	24.41	2397.29	2,000	44	<1	<1	<1	510						_
	6/14/04	2421.70	20.17	2401.53	1,500	88	<1.5	3.2	<1.5	440		-				
	12/15/04	2421.70	30.38	2391.32	1,400	46	<1	<1	<1	560						_
	6/23/05	2421.70	24.86	2396.84	1,800	41	<0.5	<0.5	<0.5	360		-				
	12/29/05	2421.70	35.04	2386.66	270	2.6	< 0.5	<0.5	<0.5	350		-				
	3/22/06	2421.70	25.69	2396.01	870	16	<0.5	<0.5	<0.5	410		-				-
	6/8/06	2421.70	14.23	2407.47	350	24	<0.5	<0.5	<0.5	120			-			-
	9/6/09	2421.70	20.69	2401.01	680	38	< 0.9	<0.9	<0.9	340		-				

Screen 20'-40'	11/23/97 12/22/97 2/1/98 2/26/98 3/14/98 4/25/98 5/16/98 7/18/98	2380.7 2380.7 2380.7 2380.7 2380.7 2380.7 2380.7 2380.7	Dry Dry Dry Dry Dry 24.44 22.21		-	(μg/L)  	-	-	(μg/L)		_	-	(μg/L)			(µg/L)
Screen 20'-40'	12/22/97 2/1/98 2/26/98 3/14/98 4/25/98 5/16/98 6/6/98 7/18/98	2380.7 2380.7 2380.7 2380.7 2380.7 2380.7 2380.7	Dry Dry Dry Dry 24.44	-								-				
Screen 20'-40'	2/1/98 2/26/98 3/14/98 4/25/98 5/16/98 6/6/98 7/18/98	2380.7 2380.7 2380.7 2380.7 2380.7 2380.7	Dry Dry Dry 24.44	-												
20'-40"	2/26/98 3/14/98 4/25/98 5/16/98 6/6/98 7/18/98	2380.7 2380.7 2380.7 2380.7 2380.7	Dry Dry 24.44	-					**							
	3/14/98 4/25/98 5/16/98 6/6/98 7/18/98	2380.7 2380.7 2380.7 2380.7	Dry 24.44									_			**	
	4/25/98 5/16/98 6/6/98 7/18/98	2380.7 2380.7 2380.7	24.44							**		-			***	
	5/16/98 6/6/98 7/18/98	2380.7 2380.7		2356.27		**						_			***	
	6/6/98 7/18/98	2380.7	22.21										***	***		
	7/18/98			2358.50	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5						
			22.63	2358.08												
	0.10 (0.0	2380.7	21.20	2359.51								_				
	9/3/98	2380.7	17.90	2362.81	<50	<0.5	< 0.5	< 0.5	< 0.5	<5						
	10/2/98	2380.7	17.21	2363.50								_			-	
	11/27/98	2380.7	26.50	2354.21				-						**	-	
	12/15/98	2380.7	27.75	2352.96	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5				**		
	1/11/00	2380.7	33.57	2347.14	880	34	<1	< 0.5	<1	170		-				
	5/4/00	2380.7	16.67	2364.04												
	6/1/00	2380.7	12.70	2368.01	<50	< 0.3	< 0.3	< 0.3	0.6	<2						
	9/26/00	2380.7	33.79	2346.92	1,430	74	< 0.3	< 0.3	< 0.6	562		_				
	12/22/00	2380.7	Dry	**												-
	3/30/01	2380.7	39.18	2341.53	1470	39.5	< 0.3	< 0.3	< 0.6	453		_				-
	6/13/01	2380.7	32.95	2347.76	520	19	<1	<1	1.1	390		-				
	9/21/01	2380.7	Dry	**								_				
	12/15/01	2380.7	Dry	**			-					-				
	3/15/02	2380.7	Dry													-
	6/26/02	2380.7	34.02	2346.69	300	11	< 0.5	< 0.5	< 0.5	280						
	9/25/02	2380.7	Dry	**			-					_				
	12/12/02	2380.7	Dry													
	(3/20/03)	2418.9	36.94	2381.97	<50	< 0.5	< 0.5	< 0.5	< 0.5	85						
	6/11/03	2418.9	17.01	2401.90	<50	< 0.5	< 0.5	< 0.5	< 0.5	39						
	9/24/03	2418.9	31.00	2387.91	180	4.1	< 0.5	< 0.5	< 0.5	82						
	12/15/03	2418.9	Dry													
	3/4/04	2418.9	28.68	2390.23	78	1.8	< 0.5	< 0.5	< 0.5	46						
	6/14/04	2418.9	22.21	2396.70	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.0						
	12/15/04	2418.9	39.94	2378.97	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	6/23/05	2418.9	28.11	2390.80	<50	0.74	< 0.5	< 0.5	< 0.5	12						
	12/29/05	2418.9	37.02	2381.89	<50	< 0.5	< 0.5	< 0.5	< 0.5	2.4						_
	3/22/06	2418.9	28.75	2390.16	<50	0.68	< 0.5	< 0.5	< 0.5	24		-	-			
	6/8/06	2418.9	12.90	2406.01	<50	< 0.5	<0.5	< 0.5	< 0.5	1.4	-	-	-		-	-
	9/6/06	2418.9	28.02	2390.89	<50	1.6	<0.5	< 0.5	< 0.5	30	-	-	-			_

Well	Sampling	TOC	DTW	GWE	TPHg		T	E	X	MTBE	TBA	DIPE	ETBE	TAME	Meth.	Eth.
No.	Date	(feet)	(feet)	(feet)	(µg/L)	$(\mu g/L)$	(µg/L)	(µg/L)								
MW-3	11/23/97	2389	38.75	2350.20	<50	< 0.5	<0.5	< 0.5	<2	16			_			-
	12/22/97	2389	39.8	2349.15							***	-				-
Screen	2/1/98	2389	39.64	2349.31	**							-				-
20'-40'	2/26/98	2389	36.06	2352.89	<50	< 0.5	0.60	0.70	< 0.5	<5						
	3/14/98	2389	34.76	2354.19												-
	4/25/98	2389	29.06	2359.89		-										-
	5/16/98	2389	27.25	2361.70	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5						-
	6/6/98	2389	28.14	2360.81					_							-
	7/18/98	2389	26.18	2362.77												
	9/3/98	2389	20.61	2368.34	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5	**					
	10/2/98	2389	19.97	2368.98												-
	11/27/98	2389	26.24	2362.71												
	12/15/98	2389	27.58	2361.37	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5						
	1/11/00	2389	30.96	2357.99	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5						
	5/4/00	2389	23.42	2365.53											-	
	6/1/00	2389	20.53	2368.42	<50	< 0.3	< 0.3	< 0.3	< 0.6	3.0						
	9/26/00	2389	28.92	2360.03	<50	< 0.3	< 0.3	< 0.3	< 0.6	9.6	-			_		
	12/22/00	2389	35.03	2353.92	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2				_		
	3/30/01	2389	36.96	2351.99	<50	< 0.3	< 0.3	< 0.3	< 0.6	5.2	-		_			
	6/13/01	2389	34.22	2354.73	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.2					-	
	9/21/01	2389	Dry	***									-	-		
	12/15/01	2389	Dry											-	-	-
	3/15/02	2389	Dry						**					-		-
	6/26/02	2389	35.43	2353.52	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5				-		-
	9/25/02	2389	39.82	2349.13	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5					**	
	12/12/02	2389	Dry	***								-				_
	(3/20/03)	2427.1	39.11	2388.01	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						-
	6/11/03	2427.1	28.24	2398.88	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	9/24/03	2427.1	30.44	2396.68	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						_
	12/15/03	2427.1	37.56	2389.56	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	3/4/04	2427.1	32.01	2395.11	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						-
	6/14/04	2427.1	26.07	2401.05	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.72						_
	12/15/04	2427.1	39.88	2387.24	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.0		-		-		-
	6/23/05	2427.1	32.93	2394.19	<50	< 0.5	< 0.5	<0.5	< 0.5	<0.5					-	
	12/29/05	2427.1	36.38	2390.74	<50	< 0.5	< 0.5	<0.5	< 0.5	0.73						
	3/22/06	2427.1	30.89	2396.23	<50	< 0.5	< 0.5	<0.5	< 0.5	<0.5			-	-		
	6/8/06	2427.1	19.71	2407.41	<50	< 0.5	<0.5	<0.5	<0.5	0.89				-		
	9/6/06	2427.1	26.64	2400.48	<50	< 0.5	< 0.5	<0.5	<0.5	0.64	-			-		

Well	Sampling	TOC	DTW	GWE	TPHg	100	T	E	X	MTBE			ETBE			Eth.
No.	Date	(feet)	(feet)	(feet)	(µg/L)	$(\mu g/L)$	(µg/L)									
MW-4	11/23/97	2373.00	Dry													
	12/22/97	2373.00	Dry											_		
Screen	2/1/98	2373.00	Dry											_	-	
20'-40"	2/26/98	2373.00	30.35	2342.65	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5					_	
	3/14/98	2373.00	23.71	2349.29			_								_	
	4/25/98	2373.00	21.16	2351.84												-
	5/16/98	2373.00	17.94	2355.06	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5		-				
	6/6/98	2373.00	16.07	2356.93			-								_	
	7/18/98	2373.00	15.75	2357.25			_			**						
	9/3/98	2373.00	12.38	2360.62	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5			-			
	10/2/98	2373.00	11.94	2361.06			_						1			-
	11/27/98	2373.00	21.04	2351.96								-				
	12/15/98	2373.00	22.21	2350.79	<50	< 0.5	< 0.5	< 0.5	< 0.5	<5						
	1/11/00	2373.00	28.38	2344.62	<50	< 0.5	< 0.5	< 0.5	<0.5	<3						
	5/4/00	2373.00	9.81	2363.19			***					_				
	6/1/00	2373.00	5.31	2367.69	<50	< 0.3	< 0.3	< 0.3	0.80	<2						
	9/26/00	2373.00	27.65	2345.35	<50	< 0.3	< 0.3	< 0.3	< 0.60	<2						
	12/22/00	2373.00	33.94	2339.06	<50	< 0.3	< 0.3	< 0.3	< 0.60	<2						
	3/30/01	2373.00	33.21	2339.79	<50	< 0.3	< 0.3	< 0.3	< 0.60	4.5						
	6/13/01	2373.00	27.22	2345.78	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.85						
	9/21/01	2373.00	Dry				**									
	12/15/01	2373.00	Dry													-
	3/15/02	2373.00	36.47	2336.53	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	6/26/02	2373.00	28.11	2344.89	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.64						
	9/25/02	2373.00	38.39	2334.61	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	12/12/02	2373.00	Dry					-								
	(3/20/03)	2411.13	31.24	2379.89	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	6/11/03	2411.13	8.30	2402.83	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	9/24/03	2411.13	24.83	2386.30	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	12/15/03	2411.13	33.11	2378.02	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5					**	
	3/4/04	2411.13	22.41	2388.72	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.3						
	6/14/04	2411.13	16.55	2394.58	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	12/15/04	2411.13	39.43	2371.70	<50	<0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	6/23/05	2411.13	22.25	2388.88	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	12/29/05	2411.13	29.83	2381.30	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	3/22/06	2411.13	22.28	2388.85	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.52			**	-		
	6/8/06	2411.13	3.76	2407.37	<50	< 0.5	<0.5	< 0.5	< 0.5	< 0.5	_					
	9/6/06	2411.13	21.49	2389.64	<50	< 0.5	<0.5	< 0.5	< 0.5	< 0.5						

Well	Sampling	TOC	DTW	GWE	TPHg		T	E	X			and the second second		TAME		Eth.
No.	Date	(feet)	(feet)	(feet)	(µg/L)	(µg/L)	(µg/L)	(µg/L)	(µg/L)							
MW-5	5/4/00	2376.9	22.92	2353.96	<50	< 0.5	<0.5	<0.5	< 0.5	< 0.5	<10	<1	<1	<1		
	6/1/00	2376.9	12.02	2364.86	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2						
Screen	9/26/00	2376.9	22.87	2354.01	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2						
15'-35'	12/22/00	2376.9	30.72	2346.16	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2		**				
	3/30/01	2376.9	Dry									**				
	6/13/01	2376.9	29.23	2347.65	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	9/21/01	2376.9	31.54	2345.34												
	12/15/01	2376.9	Dry													
	3/15/02	2376.9	Dry										-			
	6/26/02	2376.9	30.84	2346.04	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5				-		
	9/25/02	2376.9	31.52	2345.36	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	12/12/02	2376.9	Dry													
	(3/20/03)	2415	Dry													-
	6/11/03	2415	22.50	2392.54	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						
	9/24/03	2415	22.56	2392.48	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						-
	12/15/03	2415	Dry	**												
	3/4/04	2415	26.24	2388.80	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						-
	6/14/04	2415	18.92	2396.12	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5					**	
	12/15/04	2415	31.56	2383.48	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5			**		***	-
	6/23/05	2415	18.23	2396.81	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5					***	
	12/29/05	2415	31.53	2383.51	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5			**		**	-
	3/22/06	2415	25.23	2389.81	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5					**	
	6/8/06	2415	8.36	2406.68	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5			***	-	***	**
	9/6/06	2415	20.02	2395.02	<50	< 0.5	< 0.5	< 0.5	< 0.5	< 0.5						

### Table 2 GROUNDWATER ELEVATION AND ANALYTICAL DATA

Cedar Stock Resort 45810 State Highway 3 Trinity Center, California Project No. NC-017

Well No.	Sampling Date	TOC (feet)	DTW (feet)	GWE (feet)	TPHg (µg/L)		T (µg/L)	Ε (μg/L)	X (µg/L)	MTBE (μg/L)		DIPE (µg/L)	ETBE (µg/L)	TAME (µg/L)	Meth. (μg/L)	Eth. (μg/L)
MW-6	5/4/00	2379.5	22.11	2357.42	<50	< 0.5	<0.5	< 0.5	< 0.5	<0.5	<10	<1	<1	<1		
	6/1/00	2379.5	9.71	2369.82	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2			-			**
Screen	9/26/00	2379.5	24.88	2354.65	<50	< 0.3	< 0.3	< 0.3	< 0.6	2.3						
15'-35'	12/22/00	2379.5	29.47	2350.06	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2					-	
	3/30/01	2379.5	27.93	2351.60	<50	< 0.3	< 0.3	< 0.3	< 0.6	<2		_				
	6/13/01	2379.5	24.48	2355.05	<50	< 0.5	< 0.5	< 0.5	< 0.5	2.1						
	9/21/01	2379.5	32.21	2347.32	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.9						
	12/15/01	2379.5	28.43	2351.10	<50	< 0.5	< 0.5	< 0.5	< 0.5	3.2	<5	< 0.5	< 0.5	< 0.5		
	3/15/02	2379.5	24.49	2355.04	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.5						
	6/26/02	2379.5	24.85	2354.68	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.5						
	9/25/02	2379.5	32.13	2347.40	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.8						
	12/12/02	2379.5	Dry						-							
	(3/20/03)	2417.7	24.79	2392.93	<50	< 0.5	< 0.5	< 0.5	< 0.5	2.4						
	6/11/03	2417.7	11.77	2405.95	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.6						
	9/24/03	2417.7	22.95	2394.77	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.5						
	12/15/03	2417.7	No Access													
	3/4/04	2417.7	No Access					**								
	6/14/04	2418.7	15.91	2402.81	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.4						
	12/15/04	2418.7	18.28	2400.44	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.8						
	6/23/05	2418.7	18.00	2400.72	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.0						
	12/29/05	2418.7	20.08	2398.64	<50	< 0.5	< 0.5	< 0.5	< 0.5	1.3						
	3/22/06	2418.7	14.37	2404.35	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.99						
	6/8/06	2418.7	6.10	2412.62	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.80			**			
	9/6/06	2418.7	20.23	2398.49	<50	< 0.5	< 0.5	< 0.5	< 0.5	0.80						
			Taste & odo	threshold	5		42	29	17							
				MCL		1	150	750	1,750	5						
		NCR	WQCB Clea	nup Goals	<50	0.50	42	29	17	5						

Notes:

TOC: Top of casing referenced to US Bureau of Reclemation Trinity Lake level (2293.78 feet above mean sea level).

DTW: Depth to water as referenced to benchmark.

μg/L = micrograms per liter

"--": Not analyzed, available, or applicable

<###: Not detected at or below the method detection limit as shown.</p>

MCL: Maximum contaminant level, and enforcable drinking water standard

Taste & odor threshold: A drinking water standard

TPHg total pertoleum hydrocarbons as gasoline by EPA Method 8260B BTEX:Benzene, ethyl-benzene, toluene, xylenes by EPA Method 8260B

MTBE:Methyl tertiary butyl ether by EPA Method 8260B

TBA: Tert butanol by EPA Method 8260B

DIPE: Di isopropyl ether by EPA Method 8260B ETBE: Ethyl tertiary butyl ether by EPA Method 8260B

TAME: tertiary amyl methyl ether by EPA Method 8260B Meth and Eth: Methanol and Ethanol by EPA Method 8260B

NCRWQCB: North Coast Regional Water Quality Control Board

Sample date in parentheses indicated new wellhead survey per Geotracker

Table 3
INTRINSIC BIOREMEDIATION DATA
Cedar Stock Resort
45810 State Highway 3
Trinity Center, California
Project No. NC-17

Well		TPHe	МТВЕ	DO.	Eh*		Total Alkalinits	Nitrote	Ammonis	Sulfate	Ortho Phosphate	Ferrous Iron	TOC	con	BOD	Heterotrophic Plate Count		Anaerobic Hydrocarbo Degraders
No.	Date	(µg/L)	(µg/L)	(mg/L)	(mV)	рН*	(mg/L)	(mg/L)			(mg/L)	(mg/L)		(mg/L)			(CFU/mL)	
NO.	Date	(HB/L)	(HE/L)	(mg/L)	(mv)	pri	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(mg/L)	(may L)	(mg/L)	(mg/L)	(may L	(Cromic)	(Cro/ma)	(Cromit
MW-I	9/25/02	6,400	1,800	4.01	107.3	5.20	87	0.54	0.21	0.84	< 0.5	**	4.98	36		5,000	500,000	100
	12/12/02												-			-		
	3/20/03	<500	1,400	1.96	98	5.94	88	< 0.5	< 0.1	0.82	< 0.5	< 0.1	<2	17	<3	7,000	60,000	1,000
	6/11/03	420	550	1.96	305	5.86	74	< 0.5	0.58	1.3	< 0.5	< 0.1	5.2	16	3	00,000 / 35,00		35,000
	9/24/03	2,300	710	1.79	270.5	6.04		**	**	***	***						20	
	12/15/03	2,600	940	1.78	237.1	6.19				-			-					
	3/4/04	2,000	510	1.74	218.0	6.44										_		
	6/14/04	1,500	440	1.58		5.96							-					
	12/15/04	1,400	560	2.09		6.39					-	-	-			_		
	6/23/05	1,800	360	2.68		5.73								-		-	1	-
	12/29/05	270	350	7.95		4.62	_		-	_					_	_	_	_
	3/22/06	870	410	6.20		6.23	-			-		-		_				
	6/8/06	350	120	1.25	-	6.03	-	-	-							-		-
	9/6/06	680	340	4.88		5.58	-	-	-			-	-	-		-	-	
	9/0/00	1 080	340	4.00		2.20						-	**	**				**
MW-2	9/25/02											-		-				
	12/12/02										44				**			
	3/20/03	<50	85	1.88	61	6.48	95	< 0.5	0.21	0.82	< 0.5	< 0.1	3	7.9	6	20,000	4,000	500
	6/11/03	<50	39	1.88	268	6.26	73	1.1	0.17	1.10	< 0.5	< 0.1	4	<7	<3	20,000 / 200	600	4,000
	9/24/03	180	82	1.83	212.6	6.12								-				
	12/15/03	Dry no s	ample									**			**		***	200
	3/4/04	78	46	1.88	212	6.63							-	-				
	6/14/04	<50	1	1.73		6.20			-								-	
	12/15/04	<50	< 0.5													_		
	6/23/05	<50	12	1.91		5.68					**							**
	12/29/05	<50	2.40	1.50	-	4.79				-								
	3/22/06	<50	24	2.52	-	6.17				_	-	-						-
	6/8/06	<50	1.40	2.16		6.03				-								
	9/6/06	<50	30.00	2-10	-	5.71				-		-		-			-	-
MW-3	9/25/02	<50	< 0.5	4.40	228	5.12	**											
	12/12/02		**		**		**	**	***			***			**	**	**	
	3/20/03	<50	< 0.5	1.95	63	6.47							**				**	
	6/11/03	<50	< 0.5	1.92	287	6.01			***			***				**	**	***
	9/24/03	<50	< 0.5	1.91	168	6.17					**						**	
	12/15/03	<50	< 0.5	1.79	262	6.22					**						**	**
	3/4/04	<50	< 0.5	1.71	242	6.47	**	-			**							-
	6/14/04	<50	0.72	1.67		6.10			***							_	**	
	12/15/04	<50	1.00			_		-								**		
	6/23/05	<50	< 0.5	4.20		5.76												
	12/29/05	<50	0.73	6.52		4.94						**		***	**	**		**
	3/22/06	<50	< 0.5	6.41		6.07	-											
	6/8/06	<50	0.89	5.92		5.58			**						**			**
	9/6/06	<50	0.64			5.49	-											
MW-4	9/25/02	<50	< 0.5	5.40	187	5.37	78	2.9	< 0.10	1.1	< 0.5	**	<1	<10		3,000	4,000	4,000
	12/12/02			**								-	-		-			
	3/20/03	<50	< 0.5	1.82	69	6.38	68	2.2	0.13	0.79	< 0.5	<0.1	3.2	<7	<3	3,500	550	3,000
	6/11/03	<50	< 0.5	1.83	331	6.16	77	2.6	0.17	0.86	< 0.5	< 0.1	2.9	<7	<3	8,000 / 2,000	50	2,000
	9/24/03	<50	< 0.5	1.82	314.8	6.26	**				**			-				
	12/15/03	<50	< 0.5	1.72	195.1	6.08	-		**			**						10
	3/4/04	<50	1.30	1.69	208	6.77						-		-	-			
	6/14/04	<50	< 0.5	1.54	***	6.30	**	**		**	**	**		**	**	**	**	**
	12/15/04	<50	< 0.5								**		**	**	-	**	**	**
	6/23/05	<50	< 0.5	3.65		5.79							**					
	12/29/05	<50	< 0.5	6.26	_	5.88						**		-	-		**	
	3/22/06	<50	0.52	4.88		6.01						_		-	_	-		-
	6/8/06	<50	< 0.5	5.87		6.01		-		**		**	-				**	**

### Table 3 INTRINSIC BIOREMEDIATION DATA

Cedar Stock Resort 45810 State Highway 3 Trinity Center, California Project No. NC-17

Well No.	Date	TPHg (µg/L)	MTBE (µg/L)	D.O.* (mg/L)	Eh*	рН*	Total Alkalinity (mg/L)		Ammonia (mg/L)		Ortho Phosphate (mg/L)	Ferrous Iron (mg/L)	TOC (mg/L)		BOD )(mg/L)	Heterotrophic Plate Count (CFU/mL)	lydrocarbo	Degraders
MW-5	9/25/02	<50	<0.5	5.72	196	5.26		-								_		
	12/12/02				***	++			**									
	3/20/03		**			-				**	***					-		
	6/11/03	<50	< 0.5	1.95	341	6.41				-							-	
	9/24/03	<50	< 0.5	1.77	293	6.42										-		
	12/15/03	Dry no s	ample			**	14.7			-	-		_					
	3/4/04	<50	< 0.5	1.83	207	6.74					**							
	6/14/04	<50	< 0.5	1.48		6.11		***									**	
	12/15/04	<50	< 0.5		**	**					**		**					
	6/23/05	<50	< 0.5	4.10		6.14					**							
	12/29/05	<50	< 0.5	6.29		**			**									
	3/22/06	<50	< 0.5	6.20		6.32												***
	6/8/06	<50	< 0.5	6.77	**	6.47		**	**								**	***
	9/6/06	<50	< 0.5	**		5.83	**		**				**	**			-	-
MW-6	9/25/02	<50	<0.5	4.11	204	5.50	160	0.65	0.15	2.20	<0.5		<1	<10		8,000	10,000	10,000
	12/12/02							**	**								***	**
	3/20/03	<50	2.40	1.98	67	6.37	150	< 0.5	0.18	3.40	< 0.5	< 0.1	<2	10	<3	1.000	4,500	2,500
	6/11/03	<50	1.60	1.92	199	6.38	150	0.72	0.12	2.80	< 0.5	< 0.1	3.6	<7	<3	5,000 / 1,000	800	2,000
	9/24/03	<50	1.50	1.87	253.3	6.55							**			**		
	12/15/03	No acces	888													-		
	3/4/04	No acces	885	-	**													-
	6/14/04	<50	1.40	1.58		6.08							-	-				
	12/15/04	<50	1.80	2.21		**									-			_
	6/23/05	<50	1.00	3.85		5.97					**						-	
	12/29/05	<50	1.30	5.34		5.79							-					
	3/22/06	<50	0.99	6.02	_	6.61				**								
	6/8/06	<50	0.80	3.95	***	6.39												
	9/6/06	<50	0.80	3.95		6.07									-	-	_	

Notes	
TPHg	Total petroleum hydrocarbons as gasoline by EPAM 5030/8260B
MTBE	Methyl tert-butyl ether by EPA Method 8260B
µg/L	micrograms per Liter, equivalent to parts per billion - ppb
mg/L	milligrams per Liter, equivalent to parts per million - ppm
*	Parameters measured in field and recorded on field sheets
mV	Millivolts
CFU/mL	Colony forming units per milliliter
D.O.	Dissolved oxygen measured with downhole meter
Eh	Reduction-exidation potential measured with downhole meter
pH	pH measured with field meter
	1

Alkalinity by EPA Method 310.1


Nitrute by EPA Method 353.3

COD Chemical Oxygen Demand by EPA Method 410.4

Ammonia by EPA Method 350.2
Sulfiate by EPA Method 375.4
Phosphate by EPA Method 365.2
TOC Total Organic Carbon by EPA Method 415.2
Ferrous Iror by Standard Method 3500
Biological Oxygen Demand by EPA Method 405.1
Heterotrophic
Plate Count Bacteria enumeration assay by Standard Method 9215B modified Hydrocarbon
Degraders Bacteria enumeration assay for diesel and gasoline degraders
"...": Not analyzed, available, or applicable

Anti Count Bacteria enumeration assay for diesel and gasoline degraders
"...": Not analyzed, available, or applicable
Anti Count Bacteria enumeration assay for diesel and gasoline degraders
"...": Not analyzed, available, or applicable





## Site Location Map


Cedar Stock Resort 45810 State Highway 3 Trinity Center, CA


## ENVIRONMENTAL, INC.


Project No. NC-017


Report Date 9/06


Figure 1











## APPENDIX A

## GAGING DATA/PURGE CALCULATIONS

Job No.: /	VC-17	Location:	45180	Hwy 3	Trin. Ct.	Date: 9	6/06	Tech(s): J.L.
WELL NO.	DIA. (in.)	DTB (ft.)	DTW (ft.)	ST (ft.)	CV (gal.)	PV (gal.)	SPH (ft.)	NOTES
MW-1	2	40.04	20,69	19.35		9.27	0	Dy= 4,88
MW-2	1	40.11	28,02	12.09	1,93	5.79	1	DO= 2,13*
MW-3		40,97	26,64	14,33	2.29	6.87		D.0=5,75*
MW-4		40.72	G.	19.23	3.07	9.21		DO= 3.95 00
MW-5		32.10	20,02	12.08	1.93	5,79		D.O. = 5,3Z*
MW-6	V	34,79	20,23	14,56	2,32	6.96	V	D.O. = 334*
						2.5		
								1

## **Explanation:**

DIA. = Well Diameter

DTB = Depth to Bottom

DTW = Depth to Water

ST = Saturated Thickness (DTB-DTW)

CV = Casing Volume (ST x cf)

PV = Purge Volume (standard 3 x CV,

well development 10 x CV)

SPH = Thickness of Separate Phase Hydrocarbons

## Conversion Factors (cf):

2 in. dia. well cf = 0.16 gal./ft.

4 in. dia. well cf = 0.65 gal./ft.

6 in. dia. well cf = 1.44 gal./ft.



Job No.: NO	17	Location: 4	5180	Hwy 3	Date:	16/01/ Tech: JL
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	рН	
MW-1						Sample for:
Calc. purge	10:55	0.25	72	64.3	5,45	TPHg TPHd 8260
volume	11:00	4.50	142	61,1	5,47	BYEX MTBE Metals
9,27		9.25	151	61,0	5.58	Purging Method:
						PVC bailer / Pump
		S: color, turb				Sampling Method:
	Clear	/mod/	mod/s	Theen!	HOV	Dedicated / Disposable bailer
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	рН	Sample at: UITO
MW-2						Sample for:
Calc. purge	10:35	0,25	156	62,8	5,53	TPMg TPHd 8260
volume	10:40	3,00	171	60.8	5.68	BTEX MTBE Metals
5.79	10:45	5,80	191	60.1	5.71	Purging Method:
						PVC bailer / Pump
	COMMENT	S: color, turb	oidity, rechar	ge, sheen		Sampling Method:
	Clear	model	mod/	5 heen /	odor	Dedicated / Disposable bailer
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pН	Sample at: 10150
MW-3						Sample for:
Calc. purge	10:15	0,25	102	59,8	5,57	TPAg TPHd 8260
volume		3.25	81	59,1	5,48	BTEX M7BE Metals
6.87		6.85	83	58,7	5,49	Purging Method:
						PVC bailer / Pump
	COMMEN	rs: color, tur	bidity, rechar	rge, sheen		Sampling Method:
		- mod/			nogar	Dedicated / Disposable bailer
		1			V =	Sample at: 10,30

ob No.: //	C-17	Location: 4	5180 1	twy. 3	Date:	9/6/06 Tech: JL
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	рН	
MW-4						Sample for:
Calc. purge	11115	0.25	93		5,58	TPMg TPHd 8260
olume		4,50		60,3	5,61	BYEX MYBE Metals
9,21	11:25	9,20	95	59,9	5,65	Purging Method:
						PVC bailer / Pump
		S: color, turb			1100	Sampling Method:
	Clear	/mod/	mod/	Sheen/	dor	Dedicated / Disposable bailer Sample at:
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pН	1(;30
nw-5					40 to to	Sample for:
Calc. purge	11:35	0.25	115	63,7	5,74	TPMg TPHd 8260
olume	11:40	2,75	124	-	5.76	BTEX MYBE Metals
5,79	11:45	5,80	133	61.4	5.83	Purging Method:
						PVC bailer / Pump
	COMMENT	FS: color, turb	oidity, rechar	ge, sheen	1 N.O	Sampling Method:
	Clean	r/ mod	/mod/	sheen 1	odor	Dedicated / Disposable bailer
WELL No.	TIME	VOLUME (gal.)	COND. (mS/cm)	TEMP. (deg. F.)	pH	Sample at: 11:50
nw-6	-		1984.01			Sample for:
Calc. purge	11;55	0.25	201	62,4	5,93	трид трна 8260
olume		3,50		59,9	6,02	BTEX MABE Metals
6,96		7,00		0	6.07	Purging Method:
						PVC bailer / Pump
COMMENTS: cofor, turbidity, recharge, sheen						Sampling Method:
	Clear	r/mou	1/ mo	1 Shely	Moder	Dedicated / Disposable bailer
	1000	, , , , ,				Sample at: 12/10





Report Number: 52072

Date: 9/11/2006

Andrew LoCicero Blue Rock Environmental, Inc. 535 3rd Street, Suite 100 Eureka, CA 95501

Subject : 6 Water Samples Project Name : Cedar Stock Project Number : NC-17

Dear Mr. LoCicero,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed.

Kiff Analytical is certified by the State of California (# 2236). If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Project Name : Cedar Stock

Project Number: NC-17

Sample: MW-1

Matrix: Water

Lab Number: 52072-01

Report Number: 52072

Date: 9/11/2006

Sample Date :9/6/2006

Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
38	0.90	ug/L	EPA 8260B	9/9/2006
< 0.90	0.90	ug/L	EPA 8260B	9/9/2006
< 0.90	0.90	ug/L	EPA 8260B	9/9/2006
< 0.90	0.90	ug/L	EPA 8260B	9/9/2006
340	0.90	ug/L	EPA 8260B	9/9/2006
680	90	ug/L	EPA 8260B	9/9/2006
98.6		% Recovery	EPA 8260B	9/9/2006
102		% Recovery	EPA 8260B	9/9/2006
	Value  38 < 0.90 < 0.90 < 0.90 340  680	Measured Value         Reporting Limit           38         0.90           < 0.90	Measured Value         Reporting Limit         Units           38         0.90         ug/L           < 0.90	Measured Value         Reporting Limit         Units         Analysis Method           38         0.90         ug/L         EPA 8260B           < 0.90

Sample: MW-2

Matrix: Water

Lab Number: 52072-02

Sample Date :9/6/2006

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	1.6	0.50	ug/L	EPA 8260B	9/8/2006
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006
Methyl-t-butyl ether (MTBE)	30	0.50	ug/L	EPA 8260B	9/8/2006
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/8/2006
Toluene - d8 (Surr)	98.8		% Recovery	EPA 8260B	9/8/2006
4-Bromofluorobenzene (Surr)	95.9		% Recovery	EPA 8260B	9/8/2006

Approved By:

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800



Project Name: Cedar Stock

Project Number: NC-17

Sample: MW-3

Matrix: Water

Lab Number: 52072-03

Report Number: 52072

Date: 9/11/2006

Sample Date :9/6/2006

Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
0.64	0.50	ug/L	EPA 8260B	9/9/2006
< 50	50	ug/L	EPA 8260B	9/9/2006
99.2		% Recovery	EPA 8260B	9/9/2006
94.4		% Recovery	EPA 8260B	9/9/2006
	Value < 0.50 < 0.50 < 0.50 < 0.50 0.64 < 50 99.2	Measured Value Limit  < 0.50	Measured Value         Reporting Limit         Units           < 0.50	Value         Limit         Units         Method           < 0.50

Sample: MW-4

Matrix: Water

Lab Number: 52072-04

Sample Date :9/6/2006

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/9/2006
Toluene - d8 (Surr)	96.9		% Recovery	EPA 8260B	9/9/2006
4-Bromofluorobenzene (Surr)	94.8		% Recovery	EPA 8260B	9/9/2006

Approved By:

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800



Project Name : Cedar Stock

Project Number: NC-17

Sample: MW-5 Matrix: Water

Lab Number : 52072-05

Report Number: 52072

Date: 9/11/2006

Sample Date :9/6/2006

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/9/2006
Toluene - d8 (Surr)	98.3		% Recovery	EPA 8260B	9/9/2006
4-Bromofluorobenzene (Surr)	97.1		% Recovery	EPA 8260B	9/9/2006

Sample: MW-6 Matrix: Water Lab Number: 52072-06

Sample Date :9/6/2006

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006
Methyl-t-butyl ether (MTBE)	0.80	0.50	ug/L	EPA 8260B	9/9/2006
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/9/2006
Toluene - d8 (Surr)	99.8		% Recovery	EPA 8260B	9/9/2006
4-Bromofluorobenzene (Surr)	103		% Recovery	EPA 8260B	9/9/2006

Approved By:

2795 2nd St., Suite 300 Davis, CA 95616 530-297-4800

Joel Kiff

Report Number: 52072

Date: 9/11/2006

QC Report : Method Blank Data

Project Name : Cedar Stock

Project Number: NC-17

Parameter	Measured Value	Method Reporting Limit Units		Analysis Method	Date Analyzed	
Benzene	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006	
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006	
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006	
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006	
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	9/8/2006	
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/8/2006	
Toluene - d8 (Surr)	99.2		%	EPA 8260B	9/8/2006	
4-Bromofluorobenzene (Surr)	95.1		%	EPA 8260B	9/8/2006	
Benzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006	
Toluene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006	
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006	
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	9/9/2006	
Methyl-t-butyl ether (MTBE)	< 0.50	0,50	ug/L	EPA 8260B	9/9/2006	
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	9/9/2006	
Foluene - d8 (Surr)	100		%	EPA 8260B	9/9/2006	
4-Bromofluorobenzene (Surr)	103		%	EPA 8260B	9/9/2006	

Method Measured Reporting
Value Limit Units Analysis Method Date Parameter Analyzed

Approved By: Joel Kiff

Report Number: 52072

Date: 9/11/2006

Project Name : Cedar Stock

QC Report : Matrix Spike/ Matrix Spike Duplicate

Project Number: NC-17

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	e Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.		Relative	Spiked Sample Percent Recov. Limit	Relative Percent Diff, Limit
Benzene	52066-04	< 0.50	39.8	39.8	42.5	42.8	ug/L	EPA 8260B	9/8/06	107	107	0.783	70-130	25
Toluene	52066-04	< 0.50	39.8	39.8	41.7	41.1	ug/L	EPA 8260B	9/8/06	105	103	1.46	70-130	25
Tert-Butanol	52066-04	<5.0	199	199	192	192	ug/L	EPA 8260B	9/8/06	96.1	96.2	0.0933	70-130	25
Methyl-t-Butyl Eth	er 52066-04	<0.50	39.8	39.8	35.4	35.6	ug/L	EPA 8260B	9/8/06	88.9	89.3	0.458	70-130	25
Benzene	52072-06	<0.50	39.9	39.8	41.3	41.1	ug/L	EPA 8260B	9/9/06	104	103	0.106	70-130	25
Toluene	52072-06	< 0.50	39.9	39.8	43.1	42.8	ug/L	EPA 8260B	9/9/06	108	108	0.0960	70-130	25
Tert-Butanol	52072-06	<5.0	200	199	211	218	ug/L	EPA 8260B	9/9/06	106	110	3.59	70-130	25
Methyl-t-Butyl Eth	er 52072-06	0.80	39.9	39.8	35.9	35.3	ug/L	EPA 8260B	9/9/06	88.0	86.8	1.33	70-130	25

Approved By: Joe Kiff

Joe Kiff

Report Number: 52072

Date: 9/11/2006

Project Name: Cedar Stock

QC Report : Laboratory Control Sample (LCS)

Project Number: NC-17

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit	
Benzene	40.0	ug/L	EPA 8260B	9/8/06	109	70-130	
Toluene	40.0	ug/L	EPA 8260B	9/8/06	106	70-130	
Tert-Butanol	200	ug/L	EPA 8260B	9/8/06	95.8	70-130	
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	9/8/06	92.0	70-130	
Benzene	40.0	ug/L	EPA 8260B	9/9/06	104	70-130	
Toluene	40.0	ug/L	EPA 8260B	9/9/06	108	70-130	
Tert-Butanol	200	ug/L	EPA 8260B	9/9/06	104	70-130	
Methyl-t-Butyl Ether	40.0	ug/L	EPA 8260B	9/9/06	88.7	70-130	

Approved By:

Joe Kiff



Rev: 051805

2795 2nd Street, Suite 300

Davis, CA 95616

Lab: 530.297.4800 Fav: 530 207 4802 SRG # / Lab No. 52072 Page 1 of 1

		rax. J		_																															
Project Contact (Hardcopy or PDF To):  ANdrew Locicero  Company / Address: Blue Rock Env. Inc.				California EDF Report?											Chain-of-Custody Record and Analysis Request																				
Company / Address: Blue Rock Env. Inc.					Sampling Company Log Code:																		An	alys	is R	equ	est							TAT	T
535 310 ST, STE, 100 EURELIA CA																qdd							ŕ						П	Г		П		1	
Phone #: Fax #: /					Global ID: TOL OTHER IT ADDITU										u	5.0 p						(B)			Water)								12 hr		
(707) 441- 1934 (707) 441- 1949 Project #: P.O. #:					EDF Deliverable To (Email Address):											74	9						8260B)		9	W B					1				
NC-17					andrew@bluerockenv.com												1 levi						EPA	(9	8260B)	Drinking								24 hr	0
NC-17 Project Name:					Sampler Signature:											8021	qd					EDB-EPA	8260	EPA	2 Dr	=	8015M)							l s	
Project Address: 45180 Hwy 3 Trinity Center CA	<u></u>			Hame Lindermon												EPA	0.5 p			8260B)	80B)		PA	ist (	524.2	015N	A 80							For Lab Use Only	
Project Address:	Sam	pling	$\vdash$	1	Cont	aine	r	+	Pre	serv	ervative Matrix				-	) per	0	_	8260B)	4 82	4 82	A A	a) Su	E I	(EPA	A 8	(EPA	8010)	0				48 hr	N.	
45180 Hwy 3			1					1									8260B)	8260B)	8260B)	4 826	(EP	(EP	2 00	arbo	83		(E)	ō	(EPA 8	(STLC)					
Trinity Center CA			S				-	П				- 1			Н	- 1	A 8	A 8	A 82	EP (EP	ates	ates	v.(1,	aloca	rgan	rgan	esei	otor	D D					72 hr	
			Ž	8		92	ar	1	000				-		П	- 1	E (E)	E (EF	1	Gas	neg/	/gen	Sca	He H	le O	le O	as D	as M	Lea	1.5					
Sample Designation	Date	Time	40 ml VOA	Sleeve	Poly	Glass	Tedlar	9	NO.	Non			Wat	Soil	Air	- 1	MTBE (EPA	MTBE (EPA	BTEX (EPA	TPH Gas (EPA	5 Oxygenates (EPA	7 Oxygenates (EPA 8260B)	Lead Scav. (1,2 DCA & 1,2	Volatile Halocarbons (EPA	Volatile Organics Full List (EPA	Volatile Organics	TPH as Diesel (EPA 8015M)	TPH as Motor Oil	Total Lead	W.E.T. Lead				1 wk	
MW-1	9/6/06	11:10	-					7	1				X					X	X	X												П		X	0(
MW-2	1	10:50	1					1					1					1	1	1														1	02
MW-3		10:30																															-/		03
MW-4		11:30											П																						04
MW-5		11:50																																	05
MW-6	1	12:10	V					V					V					V	1	V														+	06
								Г																											
						1		T	T			1	T			$\neg$																			
						$\neg$		T				7	$\top$	$\exists$		7									$\exists$								T		
			П		П	1	$\top$	T		П		7	T	7		7	$\neg$															П	7		
Relinquished by: Date				Time Received by:										_		Rem	arks													_					
James Lindorman 9/7/			106	106 Fed Ex																															
Relinquished by: Date					Time	F	Receiv			_			_			_	_	$\dashv$																	
			_	4		4						_	_	_	-	_	_	-																	
														Bill to:																					
Relinquished by: Date				- 1	Time	F	Receiv						1	6	TH								F	or La	ıb U	se C	only:	S	amp	le R	lecei	pt			
0908			06	16 1048 Romesee Andutica							,	_	mp °		_	itials			Da	te		Tin	ne	The	erm. II	)#	Coolant	Present							
Distribution, White, Leby Blak, Originator					,	1	- Musik Lic									-91		4	40		R	La	1	09	108	:06	,	104	40	11	e-5		(es)	/ No	



